




## NVR 64ch list

تیرماه ۱۳۹۹



Model	SN-NVR2664E8
Picture	
<b>Video Input</b>	
IP Camera Input	64 Channel
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
<b>Video Output</b>	
HDMI Output	HDMI 1: 1920×1080,1440×900, 1280×1024
	HDMI 2: 3840×2160, 1920×1080,1440×900,1280×1024
VGA Output	1920×1080,1440×900, 1280×1024
Different Source Output	Support
Decoding Capacity	1ch 12MP, 4ch 8MP, 8ch 4MP, 16ch 1080P, 32ch 720P, 64ch D1
Dual Stream	Support
Multi-screen Display	1st Screen: 1/4/8/9/16/32/36/64
	2nd Screen: 1/4/8/9/16
<b>Recording</b>	
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.
Recording Mode	Manual, Schedule (Regular, Continuous), Event
Trigger Events	Motion Detection, Video Loss, Alarm in
<b>Playback and Backup</b>	
Sync Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network, eSATA
<b>Network</b>	
Interface	2 RJ-45 port (10/100/1000Mbps)
PoE	N/A
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE
Remote Users	8 users
Interoperability	ONVIF, SDK
<b>Storage</b>	
HDD	8 SATA Ports, up to 12TB for each HDD
eSATA	1 eSATA Port
Cloud Storage	Support
<b>Disk Array</b>	
Array Type	RAID 5, RAID 6, RAID 10
<b>Interface</b>	
Audio I/O	1/1
Alarm Input	16ch
Alarm Output	4ch
USB	3 ports (USB 2.0 × 2, USB3.0 × 1)
RS485	1 Port
RS232	1 Port
<b>General</b>	
Power Supply	AC100 ~ 240V
Power Consumption	< 15W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Storage Conditions	Less than 90% RH
Dimensions	440 × 433.5 × 93mm
Net Weight	7.2kg (without HDD)